


- NOTES: 1. MATERIAL:
HOUSING: POLYESTER, G.F. (UL 94V-0), COLOUR - BLACK.
TERMINAL: PHOSPHOR BRONZE.
2. TERMINAL PLATING:
90635-***1: CONTACT AREA: GOLD FLASH 0.1µm MIN.
I.D. AREA: TIN 1µm MIN. OVER
NICKEL 1µm MIN.
90635-***2: CONTACT AREA: GOLD 0.76µm MIN.
I.D. AREA: TIN 1µm MIN. OVER
NICKEL 1µm MIN.
90635-***3: CONTACT AREA: GOLD 0.38µm MIN.
I.D. AREA: TIN 1µm MIN. OVER
NICKEL 1µm MIN.
3. FOR USE WITH NO. 26 & 28 AWG STRANDED WIRE (7 CONDUCTORS)
AND NO. 28 SOLID WIRE 1.14 DIA. MAX. INSULATION RIBBON
CABLE WITH 1.27 CENTERS.
4. MATING STRAIN RELIEF: MOLEX NO. 90170.
5. DIMENSION "E" IS TOTAL HEIGHT AFTER ASSEMBLED WITH CABLE.
E= 10.5 REF. WITHOUT STRAIN RELIEF.
E= 15.2 MAX. WITH STRAIN RELIEF NO. 90170.
14.5 REF. WHEN COMPRESSED.
6. FOR PRODUCT SPECIFICATION, SEE PS: 99020-0015.

64	90635-064*	78.74	82.54	85.88	83.31
60	90635-060*	73.66	77.46	80.80	78.23
50	90635-050*	60.96	64.76	68.10	65.53
40	90635-040*	48.26	52.06	55.40	52.83
34	90635-034*	40.64	44.44	47.78	45.21
30	90635-030*	35.56	39.36	42.70	40.13
26	90635-026*	30.48	34.28	37.62	35.05
24	90635-024*	27.94	31.74	35.08	32.51
20	90635-020*	22.86	26.66	30.00	27.43
16	90635-016*	17.78	21.58	24.92	22.35
14	90635-014*	15.24	19.04	22.38	19.81
10	90635-010*	10.16	13.96	17.30	14.73
NO. OF CKT.	ENG. NO.	A	B	C REF.	D





THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION									
DIMENSION UNITS		SCALE		CURRENT REV DESC: CAD MIGRATION				molex	
mm		4:1							
GENERAL TOLERANCES (UNLESS SPECIFIED)				EC NO: 605552 DRWN: EEGBEDIRE 2018/10/04 CHK'D: TTOURISH 2019/04/15 APPR: DMAHER 2019/04/15 PRODUCT CUSTOMER DRAWING				QIK FLECS SINGLE BEAM FEMALE ASSEMBLY	
ANGULAR TOL		± °							
4 PLACES		±							
3 PLACES		±							
2 PLACES		±							
1 PLACE		±							
0 PLACES		±							
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS									
						A3-SIZE		90635	

DOCUMENT STATUS	P1	RELEASE DATE	2019/05/20	15:11:57
-----------------	----	--------------	------------	----------

- NOTES: 1. MATERIAL:
HOUSING: POLYESTER, G.F. (UL 94V-0), COLOUR - BLACK.
TERMINAL: PHOSPHOR BRONZE.
2. TERMINAL PLATING:
90635-***1: CONTACT AREA: GOLD FLASH 0.1µm MIN.
I.D. AREA: TIN 1µm MIN. OVER
NICKEL 1µm MIN.
90635-***2: CONTACT AREA: GOLD 0.76µm MIN.
I.D. AREA: TIN 1µm MIN. OVER
NICKEL 1µm MIN.
90635-***3: CONTACT AREA: GOLD 0.38µm MIN.
I.D. AREA: TIN 1µm MIN. OVER
NICKEL 1µm MIN.
3. FOR USE WITH NO. 26 & 28 AWG STRANDED WIRE (7 CONDUCTORS)
AND NO. 28 SOLID WIRE 1.14 DIA. MAX. INSULATION RIBBON
CABLE WITH 1.27 CENTERS.
4. MATING STRAIN RELIEF: MOLEX NO. 90170.
5. DIMENSION "E" IS TOTAL HEIGHT AFTER ASSEMBLED WITH CABLE.
E= 10.5 REF.WITHOUT STRAIN RELIEF.
E= 15.2 MAX. WITH STRAIN RELIEF NO. 90170.
14.5 REF. WHEN COMPRESSED.
6. FOR PRODUCT SPECIFICATION, SEE PS: 99020-0015.

64	90635-164*	78.74	82.54	85.88
60	90635-160*	73.66	77.46	80.80
50	90635-150*	60.96	64.76	68.10
40	90635-140*	48.26	52.06	55.40
34	90635-134*	40.64	44.44	47.78
30	90635-130*	35.56	39.36	42.70
26	90635-126*	30.48	34.28	37.62
24	90635-124*	27.94	31.74	35.08
20	90635-120*	22.86	26.66	30.00
16	90635-116*	17.78	21.58	24.92
14	90635-114*	15.24	19.04	22.38
10	90635-110*	10.16	13.96	17.30
NO. OF CKT.	ENG. NO.	A	B	C REF



FEMALE ASSEMBLY.
PRE-LOADED.
90635-1 ***
CIRCUIT SIZE
PLATING
OPTION

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION					
DIMENSION UNITS mm		SCALE 4:1		CURRENT REV DESC: CAD MIGRATION	
GENERAL TOLERANCES (UNLESS SPECIFIED)		EC NO: 605552		molex	
ANGULAR TOL ± °		DRWN: EEGBEDIRE 2018/10/04			
4 PLACES ±		CHK'D: TTOURISH 2019/04/15			
3 PLACES ±		APPR: DMAHER 2019/04/15			
2 PLACES ±		INITIAL REVISION:		PRODUCT CUSTOMER DRAWING	
1 PLACE ±		DRWN: POB 1990/09/25		DOCUMENT NUMBER	
0 PLACES ±		APPR: JDENNEHY 2005/08/10		SDA-90635	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION	DRAWING	SERIES	MATERIAL NUMBER
			A3-SIZE	90635	SEE CHART
					CUSTOMER
					GENERAL MARKET
					SHEET NUMBER
					2 OF 2

DOCUMENT STATUS	P1	RELEASE DATE	2019/05/20	15:11:57
-----------------	----	--------------	------------	----------

FORMAT: master-B-prod-A3
REVISION: 14
DATE: 2018/01/18

6. FOR PRODUCT SPECIFICATION, SEE PS 99020-0015.