

M4(300)-240X240T0800

Aliases (UFSM40030AT080)

EMI Suppression, KEMET, M4, Sheet, RFID

		W	T
	L		

General Information					
Series	M4				
Style	Sheet				
Description	Flex Suppressor Halogen Free Type				
Features	High Magnetic Permeability Type, Low Magnetic Loss Type				
RoHS	Yes				
Qualifications	UL94 HB, UL File No. E176124				
Environment	Halogen Free, PVC Free, Lead Free, Red Phosphorus Free				

Specifications			
Temperature Range	-40/+105°C		
Permeability	40 u At 13.56MHz		
Effective Frequency	13.56 MHz and below		
Specific Gravity	3.1TYP		
Surface Resistivity	10 MOhm/sq. TYP		

Dimensions			
Sheet Size	240x240mm		
L	240mm NOM		
W	240mm NOM		
Т	0.3mm NOM		

Packaging Specifications				
Tape Description	Without PET Tape (Txx00)			
Tape Thickness	0.03mm			
Typical Component Weight	52.45 g			

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.