

Part Number : 502128000

Series Number : 50212 Product Category : Crimp Terminals

Documents & Resources

Drawings

Drawing 502128000_sd.pdf

3D Models and Design Files

3D Model 502128000_stp.zip

Specifications

Application Specification 510900001-000.pdf
Packaging Specification SPK-50212-001-001.pdf
Product Specification 510650000-PS-000.pdf
Product Specification 510651000-PS-000.pdf
Product Specification PS-51089-001-001.pdf
Product Specification PS-51089-005-001.pdf
Product Specification PS-51090-003-001.pdf
Product Specification PS-51090-004-001.pdf
Product Specification PS-51090-005-001.pdf
Product Specification PS-51090-009-001.pdf
Product Specification PS-51090-016-001.pdf
Product Specification PS-51090-017-001.pdf
Product Specification PS-51090-018-001.pdf
Product Specification PS-51160-001-001.pdf
Product Specification PS-51160-006-001.pdf
Product Specification PS-52968-006-001.pdf
Product Specification PS-52968-007-001.pdf
Product Specification PS-53358-001-001.pdf
Product Specification PS-53717-002-001.pdf
Product Specification PS-54111-001-001.pdf
Product Specification PS-54111-002-001.pdf
Product Specification PS-54452-006-001.pdf
Product Specification PS-55533-004-001.pdf

Tooling Specifications

Application Tooling Specification 571753720ATP-E-000.pdf Application Tooling Specification 571753720ATS-000.pdf Application Tooling Specification 571753720ATP-J-000.pdf

Product Description : 2.00mm Pitch, Micro-Latch Female Crimp Terminal, Tin (Sn) Plating, 30-24 AWG, Reel Status : Active Packaging Alternative : 502128100 (Bag)

Product Environment Compliance

Compliance

GADSL/IMDS	Compliant with Exemption 44
China RoHS	®
EU ELV	Compliant per 2000/53/EC
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	Active
Category	Crimp Terminals
Series	50212
Description	2.00mm Pitch, Micro-Latch Female Crimp Terminal, Tin (Sn) Plating, 30- 24 AWG, Reel
Application	Automotive, Signal, Wire-to-Board
Product Family	Micro-Latch Wire-to-Board Connector System
Product Name	DuraClik,Mi II,Micro-Latch,Sherlock
UPC	800753644625

Electrical

Current - Maximum per Contact	2.0A
Voltage - Maximum	250V AC (RMS)/DC

Physical

Gender	Female
Material - Metal	Phosphor Bronze
Material - Plating Mating	Tin
Material - Plating Termination	Tin
Net Weight	20.400/mg
Packaging Type	Reel
Plating min - Mating	0.900µm
Plating min - Termination	0.900µm
Termination Interface Style	Crimp or Compression
Wire Insulation Diameter	1.40mm max.
Wire Size (AWG)	24, 26, 28, 30
Wire Size mm ²	N/A

Use with Part(s)

Description	Part Number
DuraClik Single Row Receptacle Housings	<u>502351</u>
Micro-Latch Single Row Receptacle Housings	<u>51065</u>
Mi II Single Row Crimp Housings	<u>51089</u>
Mi II Single Row Crimp Housings	51090

Application Tooling

Global

Description	Part Number
Extraction Tool for Micro-Fit Terminals	<u>11030043</u>
Hand Crimp Tool for 2.00mm Pitch Terminal, 30-24 AWG	<u>638190500</u>

FineAdjust Applicator for 2.00mm Pitch Wire-to-Board Crimp Terminals, 30-24 AWG Wire, Insulation OD 1.10-1.30mm	<u>639005200</u>
FineAdjust Applicator for 2.00mm Pitch Wire-to-Board Crimp Terminal, 30-24 AWG, Insulation OD 0.90-1.10mm	<u>639046800</u>
T2 Terminator Die	639105200

Application Tooling

Japan

Description	Part Number
Extraction Tool	571056000
S-1 Applicator for Wire-to-Board Receptacle Terminal, for 30-24 AWG Twisted Wire	571753720

This document was generated on Sep 15, 2024