



Technical Data

Material

Contact Material: Brass/Phosphor Bronze

Contact plating: Nicker/Gold Flash

Insulator Material: Black Polyester UL94V-0

Standard: PBT+30%G F

Electrical

Current rating: 3.0Amps/contact ma

Contact resistance: $\leq 20\text{m}\Omega$ / contact

Insulation resistance: $\geq 1000\text{M}\Omega$ at $V=100\text{V}$

Withstanding Voltage: 1000V AC/minute

Mechanical

Operating temperature: -40 C to +105C

X4602-A 1 X X

HOUSING COLOR:
B:BLACK BL:BLUE Y:YELLOW
W:WHITE GR:GREEN R:RED

CONTACT PLATING:
GF:FULL GOLD FLASH
NI:NICKEL
GN:GOLD+NICKEL

HEIGHT:
1:3.5mm

HOUSING TYPE:
A:OPEN B:CLOSE C:LONG

REVISIONS						UNSPECIFIED TOLERANCES		DSND	DATE	SCALE: N/A	MODEL TYPE:		
					ANGLAR	$\pm 5^\circ$					2.0 CONN		
ΔX					$L \leq 4$	± 0.2		DWN	DATE	VIEW:	PART NO.:		
ΔX					$4 < L \leq 16$	± 0.3		CHKD	DATE	UNIT: mm/in	DWG NO.:		
ΔX					$16 < L \leq 63$	± 0.4		APPD	DATE	SIZE: A4	X4602-A1XX		
MARK	DESCRIPTION	DATE	REVISED	APPROVED	$L > 63$	± 0.5							
www.xk-dg.cn www.helloxkb.com www.helloxkb.cn								XKB INDUSTRIAL PRECISION CO.,LIMITED			WEIGHT	SHEET	REVISION
											1.0g	1/1	A0