880584-1 ~ ACTIVE

AMP

TE Internal #: 880584-1 Novo, Closed Top, 2 Position, 2.54 mm [.1 in] Centerline, Signal, -40 – 85 °C [-40 – 185 °F], Board-to-Board Jumpers & Shunts View on TE.com >

Connectors > PCB Connectors > Board-to-Board Connectors > Board-to-Board Jumpers & Shunts



Shunt Type: Novo Shunt Style: Closed Top Number of Positions: 2 Centerline (Pitch): 2.54 mm [.1 in] Contact Current Rating (Max): 3 A

Features

Product Type Features

Connector System

Connector & Contact Terminates To

Configuration Features

Number of Positions



Board-to-Board

Printed Circuit Board

2

Electrical Characteristics

Termination Resistance	15 mΩ
Insulation Resistance	5000 ΜΩ
Body Features	
Handle	With
Primary Product Color	Black
Contact Features	
Contact Mating Area Plating Material Thickness	.381 µm[15 µin]
Contact Mating Area Plating Material	Gold
Contact Base Material	Phosphor Bronze
Shunt Type	Novo
Shunt Style	Closed Top
Contact Current Rating (Max)	3 A
Mechanical Attachment	

& For support call+1 800 522 6752

880584-1

Novo, Closed Top, 2 Position, 2.54 mm [.1 in] Centerline, Signal, -40 – 85 °C [-40 – 185 °F], Board-to-Board Jumpers & Shunts



Connector Mounting Type	Board Mount	
Housing Features		
Housing Material	Thermoplastic	
Centerline (Pitch)	2.54 mm[.1 in]	
Dimensions		
Product Height	14 mm[.551 in]	
Usage Conditions		
Operating Temperature Range	-40 – 85 °C[-40 – 185 °F]	
Operation/Application		
Circuit Application	Signal	
Industry Standards		
UL Flammability Rating	UL 94V-0	
Packaging Features		
Jumper & Shunt Packaging	Loose Piece	
Packaging Quantity	1000	
Packaging Method	Loose Piece	

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant		
EU ELV Directive 2000/53/EC	Compliant		
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold		
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC		
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free		
Solder Process Capability	Not applicable for solder process capability		

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent

880584-1

Novo, Closed Top, 2 Position, 2.54 mm [.1 in] Centerline, Signal, -40 – 85 °C [-40 – 185 °F], Board-to-Board Jumpers & Shunts



chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

Compatible Parts



Customers Also Bought



TE Part #6-1879021-1 SMW3 33R 5%	TE Part #5-103904-4 5 MTE HDR SRRA LATCH W/HLDWN	TE Part #3-794630-2 02P MICRO MNL ASSY,VRT,HDR,LF	TE Part #6339191-4 MJ,RJ45,SMT,SHLD,LED (G/Y)
201			
TE Part #2176330-5 CRGP 2010 22R 1%	TE Part #DRC13-40PA DEUTSCH DRC Headers	TE Part #2-2324245-4 ASSY,HDR,VERT,GWT,BOSSED,DUAL ROW, EP2.5	TE Part #1759503-1 mini PCI-E 8H Type I PKG G/F

Documents

Product Drawings SHUNT CONNECTOR

English

CAD Files

Customer View Model

ENG_CVM_880584-1_L.3d_igs.zip

English

880584-1

Novo, Closed Top, 2 Position, 2.54 mm [.1 in] Centerline, Signal, -40 – 85 °C [-40 – 185 °F], Board-to-Board Jumpers & Shunts



Customer View Model

ENG_CVM_880584-1_L.3d_stp.zip

English

Customer View Model

ENG_CVM_880584-1_L.2d_dxf.zip

English

3D PDF

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications Product Specification

English

Agency Approvals Agency Approval Document English