

### Catalog No. 5353

**Description:** 3/4IN INSUL 90 DEGREE LIQTIGHT CONN

**UPC No** 786210053530

**Home > Cable Protection Systems > T&B Liquidtight Fittings > Liquid tight connectors**

3/4 Inch 90 Degree Malleable Iron Insulated Liquidtight Connector



Descriptors	
Category	Liquid tight connectors
Type	Connectors-90 Degree
Application	Used where flexible metal raceway is installed in outdoor or indoor locations where exposed to continuous or intermittent moisture.
Specifications	
Material	Malleable Iron
Finish	Electro Zinc Plated/Chromate Coating
Classifications	
Brand Name	T&B Liquidtight Fittings
Standard	UL E23018, CSA
Dimensions	
Size	3/4 Inch
Compliance and Certifications	
RoHS	RoHS3 Compliant
REACH SVHC	REACH 223 Compliant
TSCA	TSCA Section 6(h) Compliant
ETIM	
ETIM	EC001180 Screw connection for protective metallic hose
Nominal size in inch	3/4 inch
Model	90°-elbow
Revolving thread	N
Construction type	External thread
Connection type screw connection to housing	Thread
Thread type	NPT

ETIM	EC001180 Screw connection for protective metallic hose
Thread connection size	Other
One-piece	N
Material housing	Other
Approved in combination with protective conduit CSA	Y
Approved in combination with protective conduit UL	Y