Product Search Data Sheet




## LFB212G45BFBD169

In Production Recommended RoHS REACH

## Appearance & Shape







Packaging	Specifications	Minimum Order Quantity
-	180mm Embossed Tape	4000



Note: This datasheet may be out of date

Co., Ltd.

Ultra-small, low-profiled, lightweight chip filters based on ceramic multilayer technology.

Please download the latest datasheet of LFB212G45BFBD169 from the official website of Murata Manufacturing

https://www.murata.com/en-us/products/productdetail?partno=LFB212G45BFBD169

Extremely ultra-small band-bass filters.

- 1. Ultra-small, low-profiled, lightweight band-pass filters.
- 2. Absolutely no adjustment required.
- 3. Reflow solderable.
- 4. Available in tape and reel packagings for automatic mounting.
- 5. Applicable for applications using frequency in the 0.5GHz to 6.0GHz.

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Product Search Data Sheet

LFB212G45BFBD169

Note: This datasheet may be out of date

Please download the latest datasheet of LFB212G45BFBD169 from the official website of Murata Manufacturing Co., Ltd. https://www.murata.com/en-us/products/productdetail?partno=LFB212G45BFBD169

## Specifications

Applications	WLAN BT	
Nominal Center Frequency(fo)	2441.00MHz	
Bandwidth(BW)	fo±39.00MHz	
Insertion Loss in BW I)	3.7dB max. (at 25°C)	
Insertion Loss in BW II)	3.9dB max. (-40 to +85°C)	
Attenuation(Absolute Value) I)	35dB min. at 880.00 to 960.00MHz	
Attenuation(Absolute Value) II)	24dB min. at 1710.00 to 1990.00MHz	
Attenuation(Absolute Value) III)	37dB min. at 4800.00 to 5000.00MHz	
Attenuation(Absolute Value) IV)	27dB min. at 7200.00 to 7500.00MHz	
Balance Impedance (Differential) (Nom.)	Conjugate match to CSR BC6888	
Unbalance Impedance (Nom.)	50Ω	
Power Capacity	500mW	
Operating Temperature Range	-40°C to 85°C	
L x W (size)	2.00x1.25mm	
Thickness(max.)	0.7mm	

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.


Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering

Product Search Data Sheet



LFB212G45BFBD169





**Frequency Characteristics** 

3 of 3

Last updated :2019/12/17

Attention

 This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Note: This datasheet may be out of date. Please download the latest datasheet of LFB212G45BFBD169 from the official website of Murata Manufacturing <u>Co., Ltd.</u> https://www.murata.com/en-us/products/productdetail?partno=LFB212G45BFBD169