



**Product:** <u>83043</u> ☑

Lead Wire, #30 Str SPC, TFE Ins, AWM 1371

Request Sample

# **Product Description**

High Temp Plastic Lead Wire, 30AWG (7x38) Silver Plated Copper, TFE Insulation, AWM 1371 105C TYPE ET MIL-W-16878/6 250V 200C

# **Technical Specifications**

### **Product Overview**

Suitable Applications: high temperature, inter-connection circuits, internal wiring of computer and electronic equipments, (Type ET) MIL-W-16878/6 applications

### **Physical Characteristics (Overall)**

#### Conductor

| AWG   | Stranding    | Material             | No. of Conductors |
|-------|--------------|----------------------|-------------------|
| 30    | 7x38         | SC - Silvered Copper | 1                 |
| Condu | ictor Count: |                      | 1                 |

### Insulation

| Material                       | Nominal Diameter | Nominal Wall Thickness |
|--------------------------------|------------------|------------------------|
| PTFE - Polytetrafluoroethylene | 0.024 in         | 0.006 in               |

### **Electrical Characteristics**

### Current

Max. Recommended Current [A]
Mil-Std-975M Table 3.16 (single wire): 1.3 A

### Voltage

UL Voltage Rating 250 V RMS

# **Temperature Range**

| Non-UL Temp Rating: | 200°C |
|---------------------|-------|
| UL Temp Rating:     | 105°C |

# **Mechanical Characteristics**

| Bulk Cable Weight:           | 0.7 lbs/1000ft |
|------------------------------|----------------|
| Min. Bend Radius/Minor Axis: | 0.1 in         |

# **Standards**

| UL AWM Style Compliance: | AWM 1371      |
|--------------------------|---------------|
| Military Compliance:     | MII-W-16878/6 |

# **Applicable Environmental and Other Programs**

| EU Directive 2000/53/EC (ELV):    | Yes |
|-----------------------------------|-----|
| EU Directive 2003/96/EC (BFR):    | Yes |
| EU Directive 2011/65/EU (RoHS 2): | Yes |

| EU Directive 2012/19/EU (WEEE):              | Yes                           |
|--|-------------------------------|
| EU Directive 2015/863/EU (RoHS 2 amendment): | Yes                           |
| EU Directive Compliance:                     | EU Directive 2003/11/EC (BFR) |
| EU CE Mark:                                  | Yes                           |
| CA Prop 65:                                  | Yes                           |
| MII Order #39 (China RoHS):                  | Yes                           |

## Flammability, LS0H, Toxicity Testing

| UL Flammability:   | WW-1      |
|--------------------|-----------|
| UL voltage rating: | 600 V RMS |

### Plenum/Non-Plenum

| Plenum (Y/N): | No |
|---------------|----|

## **Related Part Numbers**

### Variants

| Item #        | Color       | Put-Up Type | Length   | UPC          |
|---------------|-------------|-------------|----------|--------------|
| 83043 010100  | Black       | Reel        | 100 ft   |              |
| 83043 0101000 | Black       | Reel        | 1,000 ft | 612825399643 |
| 83043 005100  | Green, Dark | Reel        | 100 ft   |              |
| 83043 0051000 | Green, Dark | Reel        | 1,000 ft |              |
| 83043 002100  | Red         | Reel        | 100 ft   |              |
| 83043 0021000 | Red         | Reel        | 1,000 ft | 612825399636 |
| 83043 009100  | White       | Reel        | 100 ft   |              |
| 83043 0091000 | White       | Reel        | 1,000 ft |              |

| Footnote: E - MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 25'. |  |
|--|--|
|--|--|

## History

| Update and Revision: | Revision Number: 0.360 Revision Date: 05-05-2023 |
|----------------------|--|

#### © 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.