

Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of NCU15XH103J6SRC from the official website of Murata Manufacturing

Features

No.E137188).

2. Excellent long time aging stability

4. Flow / Reflow soldering possible5. Lead is not contained in the product.

3. High accuracy in resistance and B-constant

Co., Ltd. https://www.murata.com/en-us/products/productdetail?partno=NCU15XH103J6SRC

1. Excellent solderability and high stability in environment


6. NCU series are recognized by UL/cUL (UL1434, File

NCU15XH103J6SRC

In Production Recommended RoHS REACH AEC-

Appearance & Shape





Applications

Limited Usage	Automotive Grade
Other Usage	 Various engine control units ABS control unit High power devices (IGBT) Temperature compensation for various circuits required high temperature.

Packaging Information

Packaging	Specifications	Minimum Order Quantity
RC	180mm Paper Tape	10000



Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Product Search Data Sheet

Note: This datasheet may be out of date

Please download the latest datasheet of NCU15XH103J6SRC from the official website of Murata Manufacturing

Co., Ltd. https://www.murata.com/en-us/products/productdetail?partno=NCU15XH103J6SRC

NCU15XH103J6SRC

Specifications

Resistance (25°C)	10κΩ
Resistance Value Tolerance (at 25°C)	±5%
B-Constant (25/50°C)	3380K
B-Constant (25/50°C) Tolerance	±1%
B-Constant(25/80°C)(Reference Value)	3428K
B-Constant(25/85°C)(Reference Value)	3434K
B-Constant(25/100°C)(Reference Value)	3455K
Max. Voltage	5V
Maximum Operating Current (25°C)	0.1mA
Typical Dissipation Constant (25°C)	1mW/°C
Operating Temperature Range	-40°C to 150°C
Size Code (in mm)	1.0x0.5mm
Size Code (in inch)	0.4x0.2inch
Shape	SMD
Mass	0.0012g

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering

Product Search Data Sheet

Note: This datasheet may be out of date Please download the latest datasheet of

Please download the latest datasheet of NCU15XH103J6SRC from the official website of Murata Manufacturing Co., Ltd.


https://www.murata.com/en-us/products/productdetail?partno=NCU15XH103J6SRC


NCU15XH103J6SRC

Product Data

Ra

INNOVATOR IN ELECTRONIC





Resistance-Temperature Characteristics

Maximum Operating Voltage Reduction Characteristics

Attention

 This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
 This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering

3 of 3