TE Internal #: 1-2129458-1

Cable-to-Board, 5 Position, Jack, 25 VDC, Right Angle, Printed Circuit Board, Power & Signal, Board Mount, DC Jack Connectors


View on TE.com >



Connectors > PCB Connectors > Battery Connectors & Holders > DC Jack Connectors











Connector System: Cable-to-Board

Number of Positions: 5

Connector & Housing Type: Jack

Operating Voltage: **25 VDC**PCB Mount Retention: **Without**

PCB Contact Termination Area Plating Material

Contact Base Material

Contact Current Rating (Max)

Features

Product Type Features

Product Type Features	
Connector System	Cable-to-Board
Connector & Housing Type	Jack
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Positions	5
PCB Mount Orientation	Right Angle
Electrical Characteristics	
Operating Voltage	25 VDC
Body Features	
Primary Product Color	Yellow
Contact Features	
Contact Mating Area Plating Material	Gold

Tin

12.5 A

Copper Alloy



Mechanical Attachment

PCB Mount Retention	Without
Connector Mounting Type	Board Mount
Housing Features	
Housing Material	Thermoplastic
Usage Conditions	
Operating Temperature Range	-40 - 85 °C[-40 - 185 °F]
Operating Temperature Range Operation/Application	-40 – 85 °C[-40 – 185 °F]
	-40 – 85 °C[-40 – 185 °F] Power & Signal
Operation/Application	
Operation/Application Circuit Application	

Reel

Product Compliance

Packaging Method

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Reflow solder capable to 260°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides



on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





Customers Also Bought



















Documents

Product Drawings
DC Power Jack Conn DIP type 10.7A

English



CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-2129458-1_B_c-1-2129458-1-b.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-2129458-1_B_c-1-2129458-1-b.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-2129458-1_B_c-1-2129458-1-b.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Product Specifications

Product Specification

English

Product Specification

English