


zQSFP+/QSFP28

TE Internal #: 2334236-4 OSFP28 to SFP+ Cable Assembly, 16 Positions, 2 m [6.56 ft], 25 Gb /s, Black Cable, Shielded, 30 AWG, .051 mm², Madison TurboTwin -Round Jacketed

View on TE.com >



Cable Assemblies > Copper Cable Assemblies > Pluggable I/O Cable Assemblies > QSFP28-Four SFP+ Cable Assembly: 30 AWG



Cable Assembly Type: **QSFP28 to SFP+** Cable Assembly (End A): OSFP28 Plug

Cable Assembly (End B): SFP+ Plug

Wire Size: .051 mm²

All QSFP28-Four SFP+ Cable Assembly: 30 AWG (6)

Features

Product Type Features

Cable Assembly Category	High Speed, Industry Standard					
Cable Assembly Type	QSFP28 to SFP+					
Cable Assembly (End A)	QSFP28 Plug					
Cable Assembly (End B)	SFP+ Plug					
Cable Style	Madison TurboTwin - Round Jacketed					
Configuration Features						
Number of Positions	16					
Number of Pairs	8					
Number of Signal Positions	16					
Electrical Characteristics						
Impedance	100 Ω					
Signal Characteristics						
Data Rate	25 Gb/s					

QSFP28 to SFP+ Cable Assembly, 16 Positions, 2 m [6.56 ft], 25 Gb/s, Black Cable, Shielded, 30 AWG, .051 mm², Madison TurboTwin - Round Jacketed



Body Features

Cable Color	Black							
Cable Flammability Rating	CL2							
Equalized	No							
Dimensions								
Wire Size	.051 mm ²							
Outside Cable Diameter	4.37 mm[.172 in]							
Operation/Application								
Shielded	Yes							
Halogen Free	No							
Other								
Cable Assembly Length	2 m[6.56 ft]							
Product Compliance For compliance documentation, visit the product page on TE.com>								
EU RoHS Directive 2011/65/EU	Compliant with Exemptions							

China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold		
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Not Yet Reviewed		
Halogen Content	Not Yet Reviewed for halogen content		
Solder Process Capability	Not applicable for solder process capability		

Not Yet Reviewed

Product Compliance Disclaimer


EU ELV Directive 2000/53/EC

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked.Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

QSFP28 to SFP+ Cable Assembly, 16 Positions, 2 m [6.56 ft], 25 Gb/s, Black Cable, Shielded, 30 AWG, .051 mm², Madison TurboTwin - Round Jacketed



Compatible Parts











TE Part # 2170806-1 CAGE ASSEMBLY, 1X2, QSFP28, SPRING, HS TE Part # 2007135-1 SFP+ 1x4 CageAssembly w/ EMI gasket TE Part # 2170704-2 CAGE ASSY, QSFP28 1X1, SPRING, HS TE Part # 2227103-2 1X2 CAGE ASSY BHND BZL QSFP28




Also in the Series | zQSFP+/QSFP28

C For support call+1 800 522 6752

09/15/2024 10:12AM | Page 3

QSFP28 to SFP+ Cable Assembly, 16 Positions, 2 m [6.56 ft], 25 Gb/s, Black Cable, Shielded, 30 AWG, .051 mm², Madison TurboTwin - Round Jacketed





Customers Also Bought



A/L LOW PRO HDR 14P VERT HT	8POS MQS REC COD B	AMP DUOPLUG MK2 CONNECTOR
		5P SELECTIVE

Documents

Product Drawings QSFP TO [4]SFP 25GIG 30AWG 2 METER

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2334236-4_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2334236-4_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2334236-4_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

C For support call+1 800 522 6752

QSFP28 to SFP+ Cable Assembly, 16 Positions, 2 m [6.56 ft], 25 Gb/s, Black Cable, Shielded, 30 AWG, .051 mm², Madison TurboTwin - Round Jacketed



Product Specifications Product Specification

English

Product Specification

English