AMP | AMPSEAL

TE Internal #: 770854-1

Socket, 20 – 16 AWG Wire Size, .517 – 1.31 mm² Wire Size, Family

Seal, Tin (Sn) Interface Plating, Terminates To Wire, AMPSEAL,

Automotive Terminals

View on TE.com >



Terminals & Splices > Automotive Terminals > AMPSEAL Crimp Contacts: 1.3 mm











Terminal Type: Socket

Terminal Transmits: 0 – 24 A (Low Power)

Wire Size: .517 – 1.31 mm²

Sealable: No

All AMPSEAL Crimp Contacts: 1.3 mm (8)

Features

Product Type Features

Receptacle Style	180°
Sealable	No
Primary Locking Feature	On the Terminal

Body Features

Terminal Seal Type	Family Seal	
--------------------	-------------	--

Contact Features

Contact Size	1.3mm
Contact Fabrication	Stamped & Formed
Typical Current Rating	8 A
Crimp Type	F-Crimp
Terminal Type	Socket
Interface Plating	Tin (Sn)

Termination Features



Termination Method to Wire & Cable	Crimp
Product Terminates To	Wire
Dimensions	
Compatible Insulation Diameter Range	1.7 – 2.7 mm[.067 – .106 in]
Wire Size	.517 – 1.31 mm²
Tab Length	19.1 mm[.752 in]
Usage Conditions	
Insulation Option	Uninsulated
Operating Temperature (Max)	105 °C[221 °F]
Operating Temperature Range	-40 - 105 °C[-40 - 221 °F]
Operation/Application	
Compatible With Wire Base Material	Copper
Packaging Features	
Packaging Quantity	1000
Packaging Method	Package
Other	
Terminal Transmits	0 – 24 A (Low Power)

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts










Also in the Series | AMPSEAL



Automotive Connector Locks & Position Assurance(1)




Automotive Housings(31)



Automotive Terminals(8)








Customers Also Bought













Documents

Product Drawings

CONTACT, AMPSEAL SN/LP

English

CAD Files

Customer View Model

ENG_CVM_770854-1_O1.3d_igs.zip

English

Customer View Model

ENG_CVM_770854-1_O1.3d_stp.zip

English

Customer View Model

ENG_CVM_770854-1_O1.2d_dxf.zip

English

3D PDF

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

AMPSEAL Connector Catalog

English

ICT Terminals and Connectors Catalogue

English

CONNECTOR SELECTOR

English

Product Specifications

Socket, 20 – 16 AWG Wire Size, .517 – 1.31 mm² Wire Size, Family Seal, Tin (Sn) Interface Plating, Terminates To Wire, AMPSEAL, Automotive Terminals



Application Specification

English