

CSD-SL 300 WH - Signal light



2701785

<https://www.phoenixcontact.com/us/products/2701785>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Signal light, 24 V DC, IALA white, optimum, emission angle (vertical/Horizontal): 8 °/30 °, diameter: 272 mm, degree of protection: IP65/IP67, Communication interface

Product description

The signal lights for maritime use can be used for the reliable and energy-efficient operation of light-signal systems, such as locks. Only components that conform to the industry standard are used for the monitoring functions. The signal light 300 is available in various light colors in accordance with major standards (e.g. IALA recommendation E200-1 and CIE 1931). The fieldbus communication provides the user with a large amount of diagnostic and status information.

Your advantages

- Developed in accordance with EN 12966-1, IALA recommendation E200-1, and CIE 1931
- Failsafe function
- 400 m connection to the control unit via fieldbus
- Diagnostic capability
- High light and color intensity
- Application-specific programming supported
- Particularly economical thanks to energy-efficient LED technology and an LED service life of at least 50 000 h
- Durable and energy-saving LED technology
- Fieldbus communication
- Emission angle: 8° x 30°

Commercial data

Item number	2701785
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	DRL122
Catalog page	Page 512 (C-6-2019)
GTIN	4046356863797
Weight per piece (including packing)	4,200 g
Weight per piece (excluding packing)	4,379 g
Country of origin	DE

CSD-SL 300 WH - Signal light



2701785

<https://www.phoenixcontact.com/us/products/2701785>

Technical data

Product properties

Product type	Signaling light
Application	Maritime navigation Transportation infrastructure
Design	Operating hours counter
Special properties	Communication interface
Diagnostics messages	LEDs; temperature, current, voltage, etc. yes Mains failure, communication failure Failsafe
Light color	IALA white, optimum

Electrical properties

General

Inrush current	max. 36 A (μ -sec-pulse)
----------------	-------------------------------

Supply: Module electronics

Connection method	M17 hybrid connectors with SPEEDCON locking system
Number of positions	8
Supply voltage	24 V DC (DC)
Current consumption	max. 2.51 A (white LEDs)
Power consumption	max. 70 W (white LEDs)

Connection data

Connection method	M17 hybrid connectors with SPEEDCON locking system
-------------------	--

Signaling

Light properties

Source of light type	LED
Number of LEDs	30 (in accordance with IALA recommendation E200-1 and CIE 1931)
Service life, lighting appliance	50000 h
Light color	IALA white, optimum
Color temperature	5000 K \pm 1000 K
Color class	C3 (EN 12966)
Luminance	L3 (EN 12966)
Luminous intensity	35868 Cd
Can be dimmed	Yes, in 256 steps
Emission angle	8 ° 30 °
Luminance ratio	R3 (EN 12966)
Phantom light class	5 (EN 12368)

Diagnostic messages

CSD-SL 300 WH - Signal light



2701785

<https://www.phoenixcontact.com/us/products/2701785>

Diagnostics	LEDs; temperature, current, voltage, etc.
Message	yes

Diagnostic messages

Diagnostics	Mains failure, communication failure
Message	Failsafe

Dimensions

Depth	68 mm
Diameter	272 mm

Material specifications

Color	black (RAL 9005)
Material	Aluminum die-cast in accordance with DIN EN 1706
	Glass

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-25 °C ... 55 °C
Degree of protection	IP65/IP67 (When installed)
Air pressure (operation)	70 hPa ... 106 kPa (up to 3000 m above sea level)
Air pressure (storage/transport)	70 hPa ... 106 kPa (up to 3000 m above sea level)
Ambient temperature (storage/transport)	-25 °C ... 85 °C

Mounting

Mounting type	Screw mounting
Assembly note	Use of stainless steel fittings (corrosion-resistant)

CSD-SL 300 WH - Signal light

2701785

<https://www.phoenixcontact.com/us/products/2701785>



Classifications

ECLASS

ECLASS-11.0	27110201
ECLASS-12.0	27110201
ECLASS-13.0	27110201

ETIM

ETIM 9.0	EC002750
----------	----------

UNSPSC

UNSPSC 21.0	39111800
-------------	----------

CSD-SL 300 WH - Signal light

2701785

<https://www.phoenixcontact.com/us/products/2701785>



Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

CSD-SL 300 WH - Signal light

2701785

<https://www.phoenixcontact.com/us/products/2701785>



Accessories

ST-06KP030 - Crimp contact

1607579

<https://www.phoenixcontact.com/us/products/1607579>



Crimp contact, Pin, turned, contact diameter: 0.6 mm, crimp range: 0.34 mm² ... 0.5 mm², Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1242312

ST-10KS035 - Crimp contact

1618464

<https://www.phoenixcontact.com/us/products/1618464>



Crimp contact, Socket, turned, contact diameter: 1 mm, crimp range: 0.25 mm² .. . 1 mm², Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1243216

CSD-SL 300 WH - Signal light

2701785

<https://www.phoenixcontact.com/us/products/2701785>



ST-06KS030 - Crimp contact

1607582

<https://www.phoenixcontact.com/us/products/1607582>



Crimp contact, Socket, turned, contact diameter: 0.6 mm, crimp range: 0.34 mm² ... 0.5 mm², Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1242315

ST-10KP035 - Crimp contact

1618458

<https://www.phoenixcontact.com/us/products/1618458>



Crimp contact, Pin, turned, contact diameter: 1 mm, crimp range: 0.25 mm² ... 1 mm², Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1243215

CSD-SL 300 WH - Signal light

2701785

<https://www.phoenixcontact.com/us/products/2701785>



SF-Z0054 - Crimping pliers with digital display

1615585

<https://www.phoenixcontact.com/us/products/1615585>



Crimping pliers for turned crimp contacts \varnothing 0.6 mm / \varnothing 0.8 mm / \varnothing 1 mm / \varnothing 2 mm, litz wire cross section of 0.06 mm² ... 2.5 mm²

ST-Z0014 - Metal protective cap

1616069

<https://www.phoenixcontact.com/us/products/1616069>



Metal protective cap, M17, degree of protection: IP67, series: ST, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1243010

CSD-SL 300 WH - Signal light

2701785

<https://www.phoenixcontact.com/us/products/2701785>



ST-8EP1N8A8004S - Cable connector

1613603

<https://www.phoenixcontact.com/us/products/1613603>



Cable connector, straight, SPEEDCON, M17, number of positions: 5+3+PE, contact connection type: Pin, shielded: yes, degree of protection: IP67, cable diameter range: 8 mm ... 10 mm, number of positions: 9, connection method: Crimp connection, series: ST, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1242798

ST-8ES1N8A8004S - Cable connector

1613622

<https://www.phoenixcontact.com/us/products/1613622>



Cable connector, straight, SPEEDCON, M17, number of positions: 5+3+PE, contact connection type: Socket, shielded: yes, degree of protection: IP67, cable diameter range: 8 mm ... 10 mm, number of positions: 9, connection method: Crimp connection, series: ST, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1242805

CSD-SL 300 WH - Signal light

2701785

<https://www.phoenixcontact.com/us/products/2701785>



IBS INBC METER/E - Installation remote bus cable

2723152

<https://www.phoenixcontact.com/us/products/2723152>



By the meter, Installation remote bus cable, INTERBUS, shielded, PVC/PVC, black RAL 9005, 9-wire (3 x 2 x 0.22 mm² + 3 x 1 mm²), color single wire: green-yellow, white-brown, gray-pink, red, blue, green/yellow, for underground runs

IBS EINBC METER - Hybrid cable

2752107

<https://www.phoenixcontact.com/us/products/2752107>



INTERBUS hybrid cable for the extended installation remote bus

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com