



Catalog No. 1SVR730100R0300

Description: CT-ERS.21S Time relay, ON-delay 2c/o, 24-240VAC/DC

UPC No 4016779851442

Home > Controls & Protective Relays > Time Relays

The CT-ERS.21S is a single-function electronic time relay from the CT-S timer range. It provides an ON-delay (delay on make) function with 10 time ranges from 0.05 s to 300 h. This time relay operates with a rated control supply voltage of 24 - 240 V AC / DC and has a 2 c/o (SPDT) output with contacts rated at 250 V / 4 A. A sealable transparent cover for protection against unauthorized changes is available as accessory. The device offers screw connection technology with double-chamber cage connection terminals.

Descriptors	
Category	Time Relays
Specifications	
Rated Control Supply Voltage	24 240 volt AC / DC
Time Range	0.05 s 300 h
Product Main Type	CT-ERS
Output	2 c/o (SPDT) contacts
RoHS Status	Following EU Directive 2011/65/EU
Object Classification Code	K
Ambient Air Temperature	Operation -40 +60 °C Storage -40 +85 °C
Analog Inputs	0
Connecting Capacity UL/CSA	Flexible 1x 18-14 AWG Rigid 1x 20-12 AWG Rigid 2x 20-14 AWG
Classifications	
ETIM 4	EC001439 - Timer relay
ETIM 5.0	EC001439 - Timer relay
ETIM 6.0	EC001439 - Timer relay
ETIM 7	EC001439 - Timer relay
eClass	7.0 27371790
Dimensions	
Product Net Width	22.5 mm
Product Net Height	85.6 mm
Product Net Depth / Length	103.7 mm
· · · · · · · · · · · · · · · · · · ·	

electrification.us.abb.com Created on: 09/18/2024

Package Information

Package Information		
Package Level 1 Units	1 piece	
Package Level 1 Width	97 mm	
Package Level 1 Depth / Length	30 mm	
Package Level 1 Height	109 mm	
Package Level 1 Gross Weight	0.152 kg	
Package Level 1 EAN	4016779851442	

Ordering	
Minimum Order Quantity	1
Customs Tariff Number	85364900
ECCN	N
ECN	N
ABB MDF Code	3DL - Relays (LV / Control + Protection)
ABB Business Unit	ELSP - Smart Power

electrification.us.abb.com Created on: 09/18/2024