

**isc Silicon NPN Power Transistor**
**2SC4226**
**DESCRIPTION**


- Low Collector Current  $I_C = 0.1A$
- Low Collector Power  $P_C = 0.1W$   
With SOT-323 Package
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

**APPLICATIONS**

- Designed for broadband low noise amplifier ; wideband low noise amplifier

**ABSOLUTE MAXIMUM RATINGS ( $T_a = 25^\circ C$ )**

SYMBOL	PARAMETER	VALUE	UNIT
$V_{CBO}$	Collector-Base Voltage	20	V
$V_{CEO}$	Collector-Emitter Voltage	12	V
$V_{EBO}$	Emitter-Base Voltage	3	V
$I_C$	Collector Current-Continuous	100	mA
$P_C$	Collector Power Dissipation @ $T_C = 25^\circ C$	100	mW
$T_J$	Junction Temperature	150	$^\circ C$
$T_{stg}$	Storage Temperature Range	-65--150	$^\circ C$



DIM	MIN (mm)	MAX (mm)
A	0.20	0.40
B	1.24	1.32
C	2.06	2.21
D	1.26	1.34
H	2.08	2.16
K	0.51	0.56
L	0.80	0.90
M	0.10	0.25

**isc Silicon NPN Power Transistor**
**2SC4226**
**ELECTRICAL CHARACTERISTICS**
 $T_C=25^{\circ}\text{C}$  unless otherwise specified







SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
$V_{CB0}$	Collector-Base Voltage	$I_C=1\mu\text{A}, I_B=0$			20	V
$I_{CBO}$	Collector Cutoff Current	$V_{CB}=10\text{V}; I_E=0$			0.1	$\mu\text{A}$
$I_{EBO}$	Emitter Cutoff Current	$V_{EB}=1\text{V}; I_C=0$			1	$\mu\text{A}$
$h_{FE}$	DC Current Gain	$I_C=7\text{mA}; V_{CE}=3\text{V}$	50	150	300	
$f_T$	Current-Gain—Bandwidth Product	$I_C=7\text{mA}; V_{CE}=3\text{V}$	3.5	4.5		GHz
$C_{re}$	Output Capacitance	$I_e=0; V_{CB}=10\text{V}, f_{\text{test}}=1\text{MHz}$		0.65	1.0	pF
$ S_{21} ^2$	Power Gain	$V_{CE}=3\text{V}, I_C=3\text{mA}, f=1\text{GHz}$		8.5		dB
		$V_{CE}=3\text{V}, I_C=5\text{mA}, f=1\text{GHz}$		9		dB
		$V_{CE}=3\text{V}, I_C=7\text{mA}, f=1\text{GHz}$		9.5		dB
		$V_{CE}=3\text{V}, I_C=10\text{mA}, f=1\text{GHz}$		11		dB
NF	Noise Factor	$V_{CE}=3\text{V}, I_C=7\text{mA}, f=1\text{GHz}$		1.3	2.0	dB
		$V_{CE}=10\text{V}, I_C=5\text{mA}, f=1\text{GHz}$		1.5	2.5	dB

**◆  $h_{FE}$  Classifications**

R23	R24	R25
50-100	80-150	125-300




isc Silicon NPN Power Transistor

2SC4226



isc Silicon NPN Power Transistor

2SC4226



**isc Silicon NPN Power Transistor**
**2SC4226**
**S-PARAMETER**
 $V_{CE} = 3\text{ V}$ ,  $I_c = 7\text{ mA}$ ,  $Z_o = 50\ \Omega$ 

Freque. MHz	S <sub>11</sub>		S <sub>21</sub>		S <sub>12</sub>		S <sub>22</sub>	
	MAG	ANG	MAG	ANG	MAG	ANG	MAG	ANG
100	0.750	-45.7	11.858	144.0	0.035	63.3	0.816	-28.5
200	0.618	-84.9	10.093	122.3	0.053	53.2	0.609	-41.8
300	0.528	-114.5	8.219	107.7	0.064	50.6	0.481	-46.7
400	0.483	-134.3	6.684	97.9	0.073	50.6	0.411	-49.1
500	0.459	-148.5	5.565	90.5	0.081	50.7	0.365	-50.5
600	0.447	-158.8	4.737	84.6	0.089	52.3	0.337	-51.5
700	0.441	-167.4	4.134	79.7	0.098	53.5	0.316	-52.6
800	0.439	-174.4	3.653	75.2	0.107	54.2	0.300	-54.2
900	0.437	179.2	3.283	71.1	0.117	54.9	0.290	-55.9
1000	0.437	173.7	2.978	67.2	0.126	55.6	0.281	-57.9
1100	0.440	168.6	2.732	63.7	0.136	55.8	0.275	-59.6
1200	0.443	163.9	2.533	60.0	0.147	55.3	0.270	-62.3
1300	0.444	159.6	2.357	56.6	0.158	55.4	0.267	-64.7
1400	0.449	155.5	2.216	53.4	0.169	55.3	0.264	-67.5
1500	0.450	151.6	2.077	50.3	0.180	54.7	0.259	-70.6
1600	0.455	147.9	1.972	47.4	0.192	54.5	0.258	-73.3
1700	0.459	144.3	1.868	44.3	0.202	53.9	0.256	-76.3
1800	0.462	140.9	1.789	41.3	0.214	53.0	0.255	-79.6
1900	0.466	137.5	1.702	38.4	0.226	52.3	0.253	-83.0
2000	0.470	134.4	1.635	36.1	0.238	51.5	0.253	-86.4

**isc Silicon NPN Power Transistor**
**2SC4226**
**S-PARAMETER**
 $V_{CE} = 3\text{ V}$ ,  $I_c = 5\text{ mA}$ ,  $Z_o = 50\ \Omega$ 

Freque.	S <sub>11</sub>		S <sub>21</sub>		S <sub>12</sub>		S <sub>22</sub>	
	MAG	ANG	MAG	ANG	MAG	ANG	MAG	ANG
100	0.819	-38.9	8.934	148.0	0.038	65.8	0.868	-23.6
200	0.701	-73.4	8.007	127.6	0.060	53.1	0.687	-36.7
300	0.608	-102.3	6.898	112.6	0.072	47.6	0.560	-42.4
400	0.549	-123.6	5.819	101.8	0.079	45.2	0.483	-45.4
500	0.511	-139.6	4.970	93.5	0.086	45.7	0.434	-47.2
600	0.494	-151.0	4.255	86.9	0.093	46.5	0.402	-48.6
700	0.481	-160.8	3.750	81.4	0.099	47.2	0.379	-49.9
800	0.475	-168.6	3.328	76.3	0.107	48.9	0.361	-51.5
900	0.472	-175.7	3.004	72.0	0.113	49.7	0.350	-53.4
1000	0.471	178.2	2.734	67.7	0.122	50.9	0.340	-55.4
1100	0.473	172.8	2.522	64.0	0.130	51.6	0.332	-57.3
1200	0.474	167.6	2.355	60.2	0.139	52.3	0.328	-59.7
1300	0.474	162.9	2.176	56.7	0.148	53.1	0.322	-62.3
1400	0.477	158.4	2.038	53.2	0.158	53.3	0.319	-65.2
1500	0.481	154.4	1.921	49.8	0.168	53.7	0.315	-68.2
1600	0.484	150.3	1.818	46.7	0.177	53.3	0.313	-70.9
1700	0.489	146.5	1.726	43.9	0.190	53.3	0.312	-73.9
1800	0.490	142.9	1.647	40.6	0.200	53.0	0.312	-77.2
1900	0.495	139.3	1.578	37.6	0.212	52.7	0.309	-80.8
2000	0.501	136.0	1.505	35.0	0.223	52.0	0.309	-84.0

**isc Silicon NPN Power Transistor**
**2SC4226**
**S-PARAMETER**
 $V_{CE} = 3\text{ V}$ ,  $I_C = 3\text{ mA}$ ,  $Z_0 = 50\ \Omega$ 

Freque.	S <sub>11</sub>		S <sub>21</sub>		S <sub>12</sub>		S <sub>22</sub>	
	MAG	ANG	MAG	ANG	MAG	ANG	MAG	ANG
100	0.899	-30.6	5.578	153.7	0.042	69.0	0.923	-17.3
200	0.808	-60.6	5.327	134.4	0.069	54.5	0.793	-29.2
300	0.723	-86.7	4.877	119.6	0.084	46.0	0.679	-35.4
400	0.660	-108.2	4.341	108.1	0.093	41.1	0.604	-39.5
500	0.610	-125.9	3.883	98.5	0.098	38.8	0.550	-42.0
600	0.583	-138.6	3.388	90.9	0.102	37.4	0.513	-44.2
700	0.560	-150.0	3.046	84.3	0.106	37.8	0.487	-45.9
800	0.547	-159.4	2.741	78.5	0.108	38.1	0.468	-47.9
900	0.538	-167.4	2.498	73.4	0.112	39.5	0.455	-49.9
1000	0.535	-174.4	2.287	68.9	0.116	41.0	0.444	-52.3
1100	0.534	179.3	2.111	64.6	0.120	43.0	0.435	-54.7
1200	0.533	173.4	1.965	60.2	0.125	45.1	0.429	-57.2
1300	0.533	168.3	1.830	56.3	0.131	46.7	0.424	-59.9
1400	0.534	163.2	1.721	52.7	0.139	48.3	0.422	-62.8
1500	0.538	158.7	1.620	49.2	0.146	49.8	0.417	-65.7
1600	0.542	154.3	1.544	45.7	0.155	51.3	0.414	-68.8
1700	0.545	150.0	1.464	42.7	0.164	52.4	0.415	-72.0
1800	0.548	146.1	1.396	39.5	0.174	53.0	0.412	-75.3
1900	0.552	142.0	1.336	36.6	0.187	53.7	0.411	-78.8
2000	0.556	138.3	1.280	33.6	0.199	54.1	0.411	-82.3

**isc Silicon NPN Power Transistor**
**2SC4226**
**S-PARAMETER**
 $V_{CE} = 3\text{ V}$ ,  $I_c = 1\text{ mA}$ ,  $Z_o = 50\ \Omega$ 

Freque.	S <sub>11</sub>		S <sub>21</sub>		S <sub>12</sub>		S <sub>22</sub>	
	MAG	ANG	MAG	ANG	MAG	ANG	MAG	ANG
100	0.967	-22.9	1.935	159.9	0.045	74.0	0.978	-9.2
200	0.930	-45.8	1.968	143.1	0.083	60.1	0.931	-17.4
300	0.884	-67.1	1.938	129.1	0.108	48.9	0.870	-23.2
400	0.842	-85.9	1.827	117.2	0.125	39.4	.822	-28.0
500	0.801	-103.1	1.748	106.7	0.134	32.6	.779	-31.9
600	0.771	-117.0	1.576	97.4	0.137	27.1	0.749	-35.3
700	0.742	-130.0	1.498	89.2	0.137	22.9	0.722	-38.4
800	0.722	-141.2	1.403	81.9	0.134	20.0	0.702	-41.3
900	0.706	-151.1	1.326	75.6	0.129	18.5	0.690	-44.4
1000	0.695	-159.9	1.242	69.6	0.124	17.8	0.680	-47.4
1100	0.689	-167.7	1.169	64.5	0.118	18.1	0.671	-50.4
1200	0.685	-174.9	1.102	59.6	0.112	19.8	0.666	-53.6
1300	0.681	178.7	1.030	55.3	0.106	23.5	0.660	-56.9
1400	0.681	172.6	0.979	50.9	0.103	28.0	0.658	-60.4
1500	0.683	166.8	0.925	47.2	0.100	33.6	0.654	-64.0
1600	0.684	161.4	0.884	43.6	0.102	40.4	0.651	-67.6
1700	0.684	156.1	0.842	40.4	0.107	47.5	0.651	-71.5
1800	0.686	151.4	0.804	37.3	0.115	53.5	0.649	-75.1
1900	0.689	146.6	0.773	34.6	0.127	57.9	0.646	-79.2
2000	0.690	142.1	0.738	32.3	0.141	62.1	0.646	-83.0



**NOTICE:**

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.