


isc Triacs

BTA24-600CW

FEATURES

- With TO-220AB insulated package
- Suitable for general purpose where high surge current capability is required.
Application such as phase control and static switching on inductive or resistive load.
- Minimum Lot-to-Lot variations for robust device performance and reliable operation



ABSOLUTE MAXIMUM RATINGS(Ta=25°C)

SYMBOL	PARAMETER	MIN	UNIT
V _{DRM}	Repetitive peak off-state voltage	600	V
V _{RRM}	Repetitive peak reverse voltage	600	V
I _{T(RMS)}	RMS on-state current (full sine wave) T _j =90°C	25	A
I _{TSM}	Non-repetitive peak on-state current t _p =8.3ms	260	A
T _j	Operating junction temperature	125	°C
T _{stg}	Storage temperature	-45~150	°C
P _{G(AV)}	Average gate power dissipation(T _j =125°C)	1	W
R _{th(j-c)}	Thermal resistance, junction to case	1.5	°C/W
R _{th(j-a)}	Thermal resistance, junction to ambient	50	°C/W

ELECTRICAL CHARACTERISTICS (T_c=25°C unless otherwise specified)

SYMBOL	PARAMETER		CONDITIONS	MAX	UNIT
I _{RRM}	Repetitive peak reverse current		V _R =V _{RRM} , V _R =V _{RRM} , T _j =125°C	0.01 3.0	mA
I _{DRM}	Repetitive peak off-state current		V _D =V _{DRM} , V _D =V _{DRM} , T _j =125°C	0.01 3.0	mA
I _{GT}	Gate trigger current	I	V _D =12V; R _L = 33 Ω	35	mA
		II		35	
		III		35	
I _H	Holding current		I _{GT} = 0.5A, Gate Open	50	mA
V _{GT}	Gate trigger voltage all quadrant		V _D =12V; R _L = 33 Ω	1.3	V
V _{TM}	On-state voltage		I _T = 35A; t _p = 380 μ s	1.55	V

NOTICE:

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.