



Specifications:

规格:
 Voltage rating: 350V AC/DC
 额定电压: 350V AC/DC
 Current rating: 3A AC/DC
 额定电流: 3A AC/DC
 Withstanding voltage: 500V AC/minute
 耐受电压: 500V AC/分钟
 Temperature range: -25°C~+85°C
 温度范围: -25°C~+85°C
 Insulation resistance: ≥1000MΩ
 绝缘电阻: ≥1000MΩ
 Contact resistance: ≤20mΩ
 接触电阻: ≤20mΩ

X1511 H - XX L - N0

① ② ③ ④ ⑤

1. Series No
2. Category: H-HSG
3. Row No. Pin No: XX-02~10P
4. Special No: L-With Lock
5. Material: N0- PA66 UL94V-0 ;

Poles	Dimensions(mm)			Poles	Dimensions(mm)		
	A	B	C		A	B	C
02	1.50	4.10	3.30	09	12.00	14.60	13.80
03	3.00	5.60	4.80	10	14.0	16.10	15.30
04	4.50	7.10	6.30	11	15.0	17.60	16.80
05	6.00	8.60	7.80	12	17.0	19.10	18.30
06	7.50	10.10	9.30	13	19.0	20.60	19.80
07	9.00	11.60	10.80	14	24.0	22.10	21.30
08	10.50	13.10	12.30	15	24.0	23.60	22.80

X1511H-XXL-N0	PA66	X1511W-L	X1511T-L
PART NO	Material	Suitable XKB Wafer	Suitable XKB Terminal

广东星坤科技股份有限公司

MARK	DESCRIPTION	DATE	REVISED	APPROVED
Δ				
Δ				
Δ				

文件工程章

REVISIONS	UNSPECIFIED TOLERANCES
	ANGLAR ±5°
	L ≤ 4 ±0.2
	4 < L ≤ 16 ±0.3
	16 < L ≤ 63 ±0.4
	L > 63 ±0.5



DSND	SCALE: N/A	MODEL TYPE: 1.5mm Crimp Style Connector
DWN	VIEW:	PART NO.: X1511H-XXL-N0
CHKD	UNIT: mm/in	DWG NO.: X-X1511H-XXL-N0
APPD	SIZE: A4	WEIGHT SHEET REVISION 1/1 A0

XKB INDUSTRIAL PRECISION CO., LIMITED