


SPECIFICATIONS

- 1、Current Rating: 1A AC, DC
- 2、Voltage Rating: 50V AC, DC
- 3、Temperature Range: -25°C~+85°C
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 100MΩ Min
- 6、Withstanding Voltage: 500V AC/minute
- 7、Material: PBT, UL94V-0

编号	尺寸 (mm)	
	A	B
A1001-2X06Y	5.00	9.00
A1001-2X08Y	7.00	11.00
A1001-2X10Y	9.00	13.00
A1001-2X15Y	14.00	18.00
A1001-2X20Y	19.00	23.00
A1001-2X25Y	24.00	28.00



单位 UNIT	mm	<b>泰华电子有限公司</b> <b>TaiHua Electronics Co., Ltd</b>	
比例 SCALE	1:1		
核准: APPROVED BY	审核: CHECKED BY	版本: A0	产品名称 Production name
·xx±0.30	·xx±	页次: 1/1	1.0双排孔座
·xx±0.20	·xx±	日期: 封文辉	产品料号 Product No
·xxx±0.005, xxx±	·xxx±	制图: DRAWN BY	TH-A1001-2XY
		2022.8.31	客户料号 Client No