


PCB LAYOUT

编号	尺寸 (mm)		
	A	B	C
A1006WF-02A	1.00	4.00	3.20
A1006WF-03A	2.00	5.00	4.20
A1006WF-04A	3.00	6.00	5.20
A1006WF-05A	4.00	7.00	6.20
A1006WF-06A	5.00	8.00	7.20
A1006WF-07A	6.00	9.00	8.20
A1006WF-08A	7.00	10.00	9.20
A1006WF-09A	8.00	11.00	10.20
A1006WF-10A	9.00	12.00	11.20
A1006WF-11A	10.00	13.00	12.20
A1006WF-12A	11.00	14.00	13.20
A1006WF-20A	19.00	22.00	21.20

SPECIFICATIONS

- 1、Current Rating: 1A AC, DC
 - 2、Voltage Rating: 50V AC, DC
 - 3、Temperature Range: -25°C~+85°C
 - 4、Contact Resistance: 20mΩ Max
 - 5、Insulation Resistance: 100MΩ Min
 - 6、Withstanding Voltage: 500V AC/minute
 - 7、Material: Wafer LCP, UL94V-0
- PIN Phosphoric bronze Tin-plated
Solder tad Phosphoric bronze Tin-plated



单位
UNIT

mm

比例
SCALE

深圳市泰华电子有限公司
TaiHua Electronics Co., Ltd

X. ±0.5
X*±

批准:
APPROVED BY

版本: A0
Production name
1.0带钩贴片 WAFER SMT TYPE

. X±0.30
X*±

审核:
CHECKED BY

页次: 1/1
Product No
TH-A1006WF-NA

. XXX±0.005, XXX*±

制图:
DRAWN BY

日期: 2023.01.31
客户料号
Client No