


PCB LAYOUT

- SPECIFICATIONS
- 1、Current Rating: 1A AC, DC
 - 2、Voltage Rating: 125V AC, DC
 - 3、Temperature Range: $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$
 - 4、Contact Resistance: $20\text{m}\Omega$ Max
 - 5、Insulation Resistance: $100\text{m}\Omega$ Min
 - 6、Withstanding Voltage: 500V AC/minute
 - 7、Material: Wafer Nylon46, UL94V-0
PIN Phosphoric copper Tin-plated
Solder tads Phosphoric copper Tin-plated

编号	尺寸 (mm)	
	A	B
A1251LF-02A	1.25	7.35
A1251LF-03A	2.50	8.60
A1251LF-04A	3.75	9.85
A1251LF-05A	5.00	11.10
A1251LF-06A	6.25	12.35
A1251LF-07A	7.50	13.60
A1251LF-08A	8.75	14.85
A1251LF-09A	10.00	16.10
A1251LF-10A	11.25	17.35
A1251LF-11A	12.50	18.60
A1251LF-12A	13.75	19.85
A1251LF-15A	17.50	23.60



单位	mm
比例	1:1
SCALE	1:1
公差	X. ±0.5
	.X ±0.30
	.XX ±0.20
	.XXX ±0.005

深圳市泰华电子有限公司
TaiHua Electronics Co., Ltd

核准:	版本:	产品名称	1.25立贴封装
APPROVED BY	A0	Product name	
审核:	页次:	产品编号	TH-A1251LF-VN
CHECKED BY	1/1	Product No.	
制图:	日期:	客户编号	
DRAWN BY	2022.8.31	Client No.	

