



PCB LAYOUT

- SPECIFICATIONS
- 1、Current Rating: 4A AC, DC
  - 2、Voltage Rating: 250V AC, DC
  - 3、Temperature Range: -25°C~+85°C
  - 4、Contact Resistance: 20mΩ Max
  - 5、Insulation Resistance: 1000MΩ Min
  - 6、Withstanding Voltage: 1000V AC/minute
  - 7、Material: Wafer Nylon66, UL94V-0  
PIN Brass Tin-plated

编 号	尺寸 (mm)	
	A	B
A2542-02AW	2.54	5.08
A2542-03AW	5.08	7.62
A2542-04AW	7.62	10.16
A2542-05AW	10.16	12.70
A2542-06AW	12.70	15.24
A2542-07AW	15.24	17.78
A2542-08AW	17.78	20.32
A2542-09AW	20.32	22.86
A2542-10AW	22.86	25.40
A2542-11AW	25.40	27.94
A2542-12AW	27.94	30.48
A2542-20AW	48.26	50.80

		<b>泰华电子有限公司</b> <b>TaiHua Electronics Co., Ltd</b>	
单位 UNIT	mm	版本: VERSION	A0
比例 SCALE	1:1	产品名称 Production name	2510平弯 WAFER DIP TYPE
核准: APPROVED BY	.x.x	页次: PAGE	1/1
审核: CHECKED BY	.xx	产品料号 Product No	TH-A2542-20AW
制图: DRAWN BY	.xxx	客户料号 Client No	
	2022.3.1	日期: DATE	