



PCB LAYOUT

- SPECIFICATIONS
- 1、Current Rating: 4A AC, DC
  - 2、Voltage Rating: 250V AC, DC
  - 3、Temperature Range: -25°C~+85°C
  - 4、Contact Resistance: 20mΩ Max
  - 5、Insulation Resistance: 1000MΩ Min
  - 6、Withstanding Voltage: 1000V AC/minute
  - 7、Material: Wafer Nylon66, UL94V-0  
PIN Brass Tin-plated

编号	尺寸 (mm)	
	A	B
A2542-02AWG	2.54	5.08
A2542-03AWG	5.08	7.62
A2542-04AWG	7.62	10.16
A2542-05AWG	10.16	12.70
A2542-06AWG	12.70	15.24
A2542-07AWG	15.24	17.78
A2542-08AWG	17.78	20.32
A2542-09AWG	20.32	22.86
A2542-10AWG	22.86	25.40
A2542-11AWG	25.40	27.94
A2542-12AWG	27.94	30.48
A2542-20AWG	48.26	50.80

	单位	mm
	比例	
x ± 0.5	x ± 1	
.x ± 0.30	.x ± 1	
.xx ± 0.20	.xx ± 1	
.xxx ± 0.005, xxx ± 1		

泰华电子有限公司  
TaiHua Electronics Co., Ltd

核准: APPROVED BY	版本: A0	产品名称: 2510高弯 WATER DIP TYPE
审核: CHECKED BY	页次: 1/1	产品料号: TH-A2542-NAWG
制图: DRAWN BY	日期: 2022.3.1	客户料号: Client No