


PCB LAYOUT

SPECIFICATIONS

- 1、Current Rating: 6A AC, DC
- 2、Voltage Rating: 250V AC, DC
- 3、Temperature Range: $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$
- 4、Contact Resistance: $20\text{m}\Omega$ Max
- 5、Insulation Resistance: $1000\text{M}\Omega$ Min
- 6、Withstanding Voltage: 1500V AC/minute
- 7、Material: Wafer Nylon66, UL94V-0 PIN Brass Tin-plated

编号	尺寸 (mm)	
	A	B
A3960-02AW	3.96	7.92
A3960-03AW	7.92	11.88
A3960-04AW	11.88	15.84
A3960-05AW	15.84	19.80
A3960-06AW	19.80	23.76
A3960-07AW	23.76	27.72
A3960-08AW	27.72	31.68
A3960-09AW	31.68	35.64
A3960-10AW	35.64	39.60
A3960-11AW	39.60	43.56
A3960-12AW	43.56	47.52



单位	mm
x. ± 0.5	x. ±
.xx ± 0.30	.x ±
.xx ± 0.20	.xx ±
.xxx ± 0.005, xxx ±	.xxx ±

TaiHua Electronics Co., Ltd

标准:	A0	产品名称:	3.96平弯 WAFER DIP TYPE
审核:	1/1	产品料号:	TH-A3960-MW
制图:	封文雅	客户料号:	
日期:	2022.3.1	客户 No	