


PCB LAYOUT

- SPECIFICATIONS
- 1、Current Rating: 3A AC, DC
  - 2、Voltage Rating: 250V AC, DC
  - 3、Temperature Range: -25°C~+85°C
  - 4、Contact Resistance: 20mΩ Max
  - 5、Insulation Resistance: 1000MΩ Min
  - 6、Withstanding Voltage: 1000V AC/minute
  - 7、Material: Wafer PA6T, UL94V-0  
PIN Brass Tin-plated  
Solder tad Brass Tin-plated

编号	尺寸 (mm)		
	A	B	C
A2504WF-02A	2.50	7.50	10.00
A2504WF-03A	5.00	10.00	12.50
A2504WF-04A	7.50	12.50	15.00
A2504WF-05A	10.00	15.00	17.50
A2504WF-06A	12.50	17.50	20.00
A2504WF-07A	15.00	20.00	22.50
A2504WF-08A	17.50	22.50	25.00
A2504WF-09A	20.00	25.00	27.50
A2504WF-10A	22.50	27.50	30.00
A2504WF-11A	25.00	30.00	32.50
A2504WF-12A	27.50	32.50	35.00
A2504WF-20A	47.50	52.50	55.00



单位 mm	比例 1:1	审核: APPROVED BY	版本: NO	产品名称 Product Name	HA贴片 WAFER SMT TYPE
		核准: CHECKED BY	页次: 1/1	产品编号 Product No	TH-A2504WF-20A
		制图: DRAWN BY	日期: 2022.9.2	客户编号 Client No	

深圳市泰华电子有限公司  
**TaiHua Electronics Co., Ltd**