


PCB LAYOUT

- SPECIFICATIONS
- 1、Current Rating: 3A AC, DC
 - 2、Voltage Rating: 250V AC, DC
 - 3、Temperature Range: -25°C~+85°C
 - 4、Contact Resistance: 20mΩ Max
 - 5、Insulation Resistance: 1000MΩ Min
 - 6、Withstanding Voltage: 1000V AC/minute
 - 7、Material: Wafer LCP, PA6T, UL94V-0
- PIN Brass Tin-plated
Solder tad Brass Tin-plated

编 号	尺寸 (mm)		
	A	B	C
A2501WF-02A	2.50	7.50	10.00
A2501WF-03A	5.00	10.00	12.50
A2501WF-04A	7.50	12.50	15.00
A2501WF-05A	10.00	15.00	17.50
A2501WF-06A	12.50	17.50	20.00
A2501WF-07A	15.00	20.00	22.50
A2501WF-08A	17.50	22.50	25.00
A2501WF-09A	20.00	25.00	27.50
A2501WF-10A	22.50	27.50	30.00
A2501WF-11A	25.00	30.00	32.50
A2501WF-12A	27.50	32.50	35.00
A2501WF-20A	47.50	52.50	55.00



单位
UNIT

mm

比例
SCALE

版本: A0
Production name

TJ[C3]焊 WAFER SMT TYPE

泰华电子有限公司
TaiHua Electronics Co., Ltd

x. ±0.5 x* ±

核准:
APPROVED BY

版本: A0

产品名称
Product name

TJ[C3]焊 WAFER SMT TYPE

.x ±0.30 x* ±

比例:
CHECKED BY

页次: 1/1

产品料号
Product No

TH-A2501WF-NA

.xxx ±0.003 .xxx ±

制图:
DRAWN BY

日期: 2022.9.6

客户料号
Client No