




THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.


REV.	ECN NO.	DATE	SIGN	DESCRIPTION
A		2020/01/20	Vicky	Initial Released
B	C220646	2022/04/28	Vicky	$\triangle B$ X2
C	C221777	2022/11/15	Vicky	$\triangle C$ X4



C2  
Pin Assignments  
Front View



C1  
Pin Assignments  
Front View



AB-BBD XX ML-BBDFL-QF XXX

$\triangle B$  XX: No. Of Pin

XXX: 0.5~99Meters  
 A05: 0.5 Meter  
 001: 01 Meter  
 002: 02 Meters  
 :  
 099: 99 Meters

6	Blue (26AWG)	藍	Twist 對線
5	Red (26AWG)	紅	
4	Green (26AWG)	綠	Twist 對線
3	White (26AWG)	白	
2	Black (16AWG)	黑	
1	White (16AWG)	白	
C1 & C2	Wire Color		
Pin Out			

- Note:
- \* RoHS Compliant
  - \*  $\odot$  Important dimension
  - \* C1  
 Waterproof rate: IPX8, mated 1m/24h  
 Housing: Thermoplastic, Black  
 Pin: Copper alloy, Gold plated  
 Outer Mold: Thermoplastic, Black
  - \* C2  
 Waterproof rate: IPX8, mated 1m/24h  
 Housing: Thermoplastic, Black  
 Pin: Copper alloy, Gold plated  
 O-Ring: Rubber, Dark gray  
 Nut: Thermoplastic, Black  
 Outer Mold: Thermoplastic, Black
  - \* Cable: UL21996, 16#\*2C+AL/MY+(26#\*2P+AL/MY), PVC Jacket, Black, OD9.3mm
  - \* Cable length tolerance: 0.5M < L ≤ 1M: +60/-0 mm  
 1M < L ≤ 3M: +120/-0 mm  
 3M < L ≤ 5M: +160/-0 mm  
 5M < L ≤ 10M: ±100 mm  
 10M < L ≤ 20M: ±200 mm  
 20M < L ≤ 30M: ±300 mm  
 30M < L ≤ 99M: ±500 mm

UNIT:mm		TITLE ACC, XLOK, B-10A+5A, DB-ENDED MF	<b>Amphenol LTW</b>		ITEM NO	DRAWN BY Vicky	DATE 2020-01-20
TOLERANCE ±0.5mm		SCALE 1:2	SIZE A4	SHEET 1 OF 1	DWG NO AB-BBDXXML-BBDFL-QFXXX	CHECKED BY Rita	DATE 2020-01-20
		REV. C	WC-REV. A.5	$\odot$ : Inspection item	CUSTOMER ALTW	APPROVED BY Max	DATE 2020-01-20

安費諾亮泰企業股份有限公司